

TIP1500 & 3500

THERMAL INSULATOR PAD WITH HIGH THERMAL CONDUCTIVITY

Solstice's TIP1500 & TIP3500 thermal insulators are designed to provide low thermal impedance and high isolation for high power and high voltage applications. Integrated fiberglass reinforcement protects the pad from tears, cut-throughs and punctures. TIP1500 and TIP3500 are designed to be soft and conformal which provide excellent mating surface for low pressure mounting. TIP1500 only offers 0.19mm and 0.23mm thickness. TIP3500 offers in thicknesses ranging from 0.25mm to 0.50mm.

STORAGE & USE: Shelf life 12 months at 23 ±2°C



Typical Applications:

- Automotive electronics
- Power conversion equipment
- Power supply equipment
- Motor controllers
- Speaker amplifier
- Power switch

PROPERTY		TIP1500	TIP3500	TEST METHOD
Color		Pink	Blue	Visual
Thickness (mm)		0.19, 0.23	0.25-0.50	ASTM D374
Specific Gravity		2.21	2.47	ASTM D792
Hardness (Shore A)		90	80	ASTM D2240
Thermal Conductivity (W/m·K)		1.5	3.5	ASTM D5470
Thermal Impedance	°C·in ² /W @10psi (Typical Value)	0.91@0.19mm 0.93@0.23mm	0.23	ASTM D5470
	°C·in ² /W @50psi (Typical Value)	0.54@0.19mm 0.61@0.23mm	0.18	
Breakdown Voltage (Vac)		>6000	>6000	ASTM D149
Dielectric Constant@1MHz		5.50	3.30	ASTM D150
Volume Resistivity (Ohm·cm)		1 x 10 ¹³	5 x 10 ¹³	ASTM D257
Flammability Rating		V-0	V-0	UL94

FEATURES & BENEFITS

- High thermal performance
- High breakdown voltage
- Good resistant to tears, cut-throughs and punctures
- Single side PSA available for easy assembly



All statements and information provided herein are believed to be accurate and reliable, but are presented without guarantee, warranty, or responsibility of any kind, express or implied. Statements regarding possible uses of our products are provided for informational purposes only and do not constitute a representation or warranty. Users remain responsible for evaluating all safety and environmental considerations. Any descriptions of future products, intended updates, or improved features or functions do not constitute a commitment by Solstice to develop, sell, or release such products, updates, features, or functions, as such decisions remain in our sole discretion. © 2026 Solstice Advanced Materials US, Inc.



For More Information Visit
solstice.com

Solstice Advanced Materials Inc.
115 Tabor Rd. | Morris Plains, NJ 07950



© 2026 Solstice Advanced Materials Inc.
6230505-esm-tds-tip1500-3500-ltr-en | SOLS | 06/26