

HYDROBLOCK® PS SERIES FILM

HydroBlock® PS Series film is a high-performance structure combining a polychlorotrifluoroethylene (PCTFE) durable cover film layered with an outdoor grade of pressure-sensitive adhesive + a peelable PET liner, allowing efficient and simple field application to a variety of surfaces. The structure offers excellent clarity and moisture barrier combined with world-class leading chemical, stain, and UV resistance for graffiti removability, protection of graphics, preservation of sensitive electronics and phosphors, and retention of low temperature flexibility. PS4000N is designed for harsh environments where high levels of moisture protection and abrasion resistance are desired.

PROPERTIES	PS2000N	PS4000N
PCTFE Film Thickness	2 mil	4 mil
24hr 180° Peel (*PSTC 101)	≥ 90 oz/in	
Application Temperature	>50°F	
Shelf Life (RT, 50%RH)	2 years	
Shrinkage 10 min @ 300°F Laminated to Metal	MD +0.5%; TD -0.1%	
Water Vapor Transmission Rate	gms/100in²/day	gms/100in²/day
@77°F /60% RH	0.0012	0.0006
@100°F /100% RH	0.0077	0.0042

*Pressure Sensitive Tape Council
www.pstc.org



All statements and information provided herein are believed to be accurate and reliable, but are presented without guarantee, warranty, or responsibility of any kind, express or implied. Statements regarding possible uses of our products are provided for informational purposes only and do not constitute a representation or warranty. Users remain responsible for evaluating all safety and environmental considerations. Any descriptions of future products, intended updates, or improved features or functions do not constitute a commitment by Solstice to develop, sell, or release such products, updates, features, or functions, as such decisions remain in our sole discretion. © 2026 Solstice Advanced Materials US, Inc.



For More Information Visit
solstice.com

Solstice Advanced Materials Inc.
115 Tabor Rd. | Morris Plains, NJ 07950

