

RL 185 WAX BLEND

TECHNICAL DATA SHEET

RL 185 is an external lubricant for rigid PVC compounds. More efficient than RL 165 and particularly suitable for high shear extrusion applications.

Safety Precautions: Consult our Material Safety Data Sheet for specific recommendations on safe handling.

TYPICAL PROPERTIES

PROPERTY	VALUE	TEST METHOD
Congealing Point, °C (°F)	87.4 °C (189 °F)	ASTM D938
Viscosity, Kinematic at 240 °F, cSt	7.7	ASTM D445

REGULATORY COMPLIANCE

APPROVAL TYPE	VALUE	PPI/NSF USE LEVEL
Plastic Pipe Institute/NSF	No	

PRODUCT FORM

PROPERTY	VALUE
Product Form	Prills



All statements and information provided herein are believed to be accurate and reliable, but are presented without guarantee, warranty, or responsibility of any kind, express or implied. Statements regarding possible uses of our products are provided for informational purposes only and do not constitute a representation or warranty. Users remain responsible for evaluating all safety and environmental considerations. Any descriptions of future products, intended updates, or improved features or functions do not constitute a commitment by Solstice to develop, sell, or release such products, updates, features, or functions, as such decisions remain in our sole discretion. © 2026 Solstice Advanced Materials US, Inc.



For More Information Visit
solstice.com

Solstice Advanced Materials Inc.
115 Tabor Rd. | Morris Plains, NJ 07950



© 2026 Solstice Advanced Materials US, Inc.
10460005-esm-tds-rl-185-ltr-en | SOLS | Aug2026